

## RTxSC3 Technical specifications

	RTLx-SC3	RTKx-SC3
<b>Operating data</b>		
Operating weight lb	3,295	3,235
L x W x H in	73 x 32 x 50	73 x 32 x 50
Drum diameter in	20.5	20.5
Width Drum in	22 / 32*	22 / 32*
Centrifugal force (min.) lbf	7,700	7,700
Centrifugal force (max.) lbf	15,400	15,400
Frequency Hz	41.7	41.7
Linear force static (per drum) lb/in	58.3	56.2
Linear force dynamic (per drum) lb/in	258	258
Travel speed forward mph	1.5	1.5
Travel speed reverse mph	1.5	1.5
Turning radius inner in	63	63
Surface capacity max. (depending on soil consistency) ft <sup>2</sup> /h	10,654	10,654
Gradeability max. (without vibration) %	50	50
Gradeability max. (with vibration) %	45	50
<b>Engine / Motor</b>		
Engine / Motor type	Water-cooled 3-cylinder diesel engine with electric starter	Water-cooled 3-cylinder diesel engine with electric starter
Engine / Motor manufacturer	Kohler KDW 1003	Kubota D902
Displacement in <sup>3</sup>	62.7	54.8
Operating performance (DIN ISO 3046) hp	19.8	20.8
RPM / speed Operating rpm	3,000	3,000
Fuel type Low Sulfer / Ultra Low Sulfer	Diesel	Diesel
Fuel consumption US gal/h	1.2	1.2
Tank capacity US gal	6.3	6.3

\*RTx model drums can be configured for 32in (820mm) or 22in (560mm) width.

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2020 Wacker Neuson SE.